

18 TO 32 ZONE FIRE ALARM PANEL

MODEL - MS-232

Reliable Protection for
Safer Buildings

FEATURES

-  Zone wise Fire, Fault LED indication.
-  Zone isolation facility.
-  Auto dialer attachable facility.
-  External s/w for reset, Silence, Lamp test.
-  16x2 line LCD display, inbuilt buzzer.
-  Inbuilt battery charger & battery space.
-  Operates on 230 V AC, 50 Hz AC supply.
-  Potential free contact facility.
-  It can support up to 20 devices in each zone.
-  Mains, AC fail, fuse, charging, low battery indication.
-  Zone wise hooter option along with common hooter.



MECHANICAL SPECIFICATION

Cabinet Type	MS
Colour	OFF white / Red / Dark Grey
Paint	Powder Coating
Knock Out	18mm
Dimensions	226 x 171 x 54mm
Weight	10kg without battery

TECHNICAL SPECIFICATION

Power I/p	230V AC / 24V dc optional
Power Consumption	75 watt
End of Line	4x7
No. of Zones	18 - 32
Detection O/P Supply	24V dc
Hooter O/P Supply	24V dc
Operating Temperature	0 - 60°
Operating Humidity	95% (Non condensing)



**EARLY
DETECTION**



**ENHANCED
SAFETY**



**IDEAL FOR
COMMERCIAL & INDUSTRIAL**



**RELIABLE
PERFORMANCE**